

Arborist 130

Entry level – but not to be under-estimated

GreenMech
The Professionals' Choice



Customer category

Landscaper • Estate Maintenance • Contractor

Professional site clearance contractors, arborists and hire companies looking for a wood chipper that handles up to 150mm with ease, the GreenMech Arborist 130 is the smallest GreenMech in the road-tow sector but capable of very high output. Importantly, it's construction is identical to that of its bigger brother, the only significant difference being that it is powered by a 23hp Honda petrol engine and therefore enters a lower price bracket, but with long-term durability and excellent performance. The specially designed engine cover not only provides component protection from the elements but also arrests engine noise to minimise sound levels at the operator's ear. Unlike most competitors, the 130 comes fitted standard with both parking brake and over-run brakes for safe road transportation.

The backbone of the Arborist 130s design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 970mm x 790mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through twin, hydraulically powered feed rollers, the patented electronically controlled No-Stress system automatically manages the throughput of material to maximise chipping efficiency.

Arborist 130

Technical Specification...

GreenMech
The Professionals' Choice

Key features

- ⊙ 150mm chipping capacity
- ⊙ 23hp Honda Petrol engine
- ⊙ Disc-blade chipping technology
- ⊙ Twin hydraulic feed rollers
- ⊙ No-Stress power control
- ⊙ Bottom-bar safety mechanism
- ⊙ 670kg weight



Capacity	150mm
Engine Make	Honda
Engine	23hp
Fuel	Petrol
Tractor Required	n/a
Chipping Flywheel	Disc Type
Flywheel Speed	1800rpm
Blades	4
Hydraulic Feed Rollers	Twin Vertical
Turntable	n/a
Power Control	No-Stress
Fuel Capacity (engine)	27 L
Tyre Size (towed)	155/80/R13
Spare Wheel	Optional
Tonnes per hour	3

Infeed Chute Aperture	970mm x 790mm
Infeed Throat Size	150mm x 230mm
Bottom-bar safety mechanism	Standard
Discharge Chute	280° Rotation
Hydraulic Oil Capacity	30 L
Clutch	n/a
Hour Meter	Standard
Length (transport)	3556mm
Width (transport)	1290mm
Height	2335mm
Weight	670kg
Sound Power LWA	116dB(A)
Sound Pressure LPA	92dB(A)
Parking Brake	Standard
Over-run Brake	Standard